

### **Amendments to the Specification**

Please replace the paragraph beginning at page 27, line 14, with the following amended paragraph:

-- Next, the arrangement and the configuration of the rear cushion for the rear wheel ~~64~~ 63 will be described. --

Please replace the paragraph beginning at page 27, line 16, with the following amended paragraph:

-- Fig. 24 is a schematic diagram showing the low floor type vehicle according to an embodiment of the invention and shows that the housing box 59 having substantially similar longitudinal length to the longitudinal length of the seat 58 is provided under the seat 58 and the rear cushion 61 for the rear wheel ~~64~~ 63 is transversely arranged under the housing box 59. Fig. 13 shows that the rear cushion 61 is arranged substantially in the center of the body (in the center in the width of the body). --

Please replace the paragraph beginning at page 27, line 25, with the following amended paragraph:

-- The rear cushion for the rear wheel ~~64~~ 63 is arranged along the rear of the upper frame 22. Detailedly, the rear cushion 61 is arranged over the upper frame 22 and substantially in parallel with the upper frame 22 by coupling one end of the rear cushion 61 to the bracket for the cushion 34 of the upper frame 22 and coupling the other end of the rear cushion 61 to a bracket for a cushion 167 of the swing arm 62. --

Please replace the paragraph beginning at page 28, line 10, with the following amended paragraph:

-- As the rear cushion for the rear wheel ~~64~~ 63 is transversely (horizontally) arranged under the housing box 59, the housing box does not interfere with the rear cushion for the rear wheel

64 63 located substantially in the center of the body even if the housing box 59 is longitudinally extended. Therefore, the housing box 59 having the substantially similar longitudinal length to the longitudinal length of the seat 58 can be arranged under the seat 58. Therefore, housing space for housing a long thing having a large diameter can be easily secured by extending the housing box 59 longitudinally and expanding the housing space. --